

Issue 20170411 – April 2017

SSEN-2G-LS



smartengine Sensor Pod, Generation 2, in custom color with custom cable length

- Transfers up to 34 W to fixture
- Light level sensor
- Ambient temperature sensor
- Infrared motion sensor

GENERAL SPECIFICATIONS

Brand	smartengine
Generation	2
Product Type	Sensor Pod
Application	Collects sensor data
Includes	Collar RJ25 cable
Data Ports, qty	1
Colour	White
Mount Type	Ceiling
Package Quantity	1
Ordering Note	Available in Asia Pacific Available in Europe Available in the United States and Canada

DIMENSIONS

Cable Length	2.1 m 7.0 ft
Height	45.72 mm 1.80 in
Inner Diameter	25.40 mm 1.00 in
Outer Diameter	40.64 mm 1.60 in
Weight	0.11 kg 0.25 lb

MECHANICAL SPECIFICATIONS

Sensor Connector Interface	RJ25
Material Type	Plastic

ELECTRICAL SPECIFICATIONS

ANSI/TIA Category	5e 6 6A
Power Consumption, max.	10 mW

Issue 20170411 – April 2017

SSEN-2G-LS

ENVIRONMENTAL SPECIFICATIONS

Ambient Temp. Sensor Range 0°C to +100°C (+32°F to +212°F)

Amb. Temp. Sensor Tolerance ±2 °C (3.6 °F)

Environmental Space..... Indoor | Plenum

Operating Humidity 10%-80%, non-condensing

Operating Temperature 0°C to +50°C (+32°F to +122°F)

Storage Humidity 5%-95%, non-condensing

Storage Temperature -20°C to +60°C (-4°F to +140°F)

Safety Standard..... AS/NZS CISPR 22 | c-UL-us | CE | CEC Title 24-2008 | IEC 60950 | IEC 61000-4.5, Class 3 | UL 60950 | UL 924 | UL-us | US FCC Part 15, Class A

SSEN-2G-LS

REGULATORY COMPLIANCE/CERTIFICATIONS

Agency	Classification
RoHS 2011/65/EU	Compliant

